




“Specialists in Expanded Metal Building Products”

DOUBLE “V” INSIDE CORNER EXPANSION CONTROL JOINT - Zinc



Double V Expansion Control Joint – Inside Corner	Length	Ctns/Pallet	Nominal Lbs/Ctn	Nominal WT/Pallet
1/2”	10’	40	58	2320
5/8”	10’	40	63	2520
3/4”	10’	40	68	2720
7/8”	10’	40	72	2880

24pcs/ctn – 240’ per ctn

The Double “V” Expansion Control Joint is used to provide mechanism for movement to accommodate expansion and contraction caused by initial stucco shrinkage and minor thermal movement. It is roll formed to fit inside corner locations.

ASTM C653 - Standard specification for steel sheet, zinc-coated (galvanized) or zinc-iron alloy coated (galvannealed) by the hot-dip process.

ASTM C841 - Standard specification for installation of interior lathing and furring.

ASTM C1063 - Standard specification for installation of lathing and furring for portland cement-based plaster

NILES BUILDING PRODUCTS CO.

Company Headquarters
1600 Hunter Street
Niles, Oh 44446

Dallas/Fort Worth Service Center
6400 Wuliger, Ste A
North Richland Hills, TX 76180

Southeast Distribution Center
1325 Cobb International Dr
Kennesaw, GA 30152

Phone: 800-323-3329

Fax: 330-544-8868

www.nilesbldg.com