




**“Specialists in Expanded Metal Building Products”**

## **NILES ZINC CONTROL JOINT**



<b>Niles Zinc Control Joint</b>	<b>Length</b>	<b>Ctns/Pallet</b>	<b>Nominal Lbs/Ctn</b>	<b>Nominal Lbs/Plt</b>
C380 – 3/8" GR	10'	20	55	1100
C500 – 1/2" GR	10'	20	60	1200
C750 – 3/4" GR	10'	20	66	1320

25pcs/ctn – 250' per ctn

Used to provide a mechanism for movement to accommodate expansion and contraction caused by initial stucco shrinkage and minor thermal movement. The "J" shaped shoulder provides excellent stucco bonding. The Niles Zinc Control Joint has unexpanded flanges with large holes that aid in the bonding to adjoining metal lath. Comes pre-taped to ensure a clean finish.

ASTM B69-87 - Standard specification for flat rolled zinc. Approximately 99% pure zinc

## **NILES BUILDING PRODUCTS CO.**

Company Headquarters  
1600 Hunter Street  
Niles, Oh 44446

Dallas/Fort Worth Service Center  
6400 Wuliger, Ste A  
North Richland Hills, TX 76180

Southeast Distribution Center  
1325 Cobb International Dr  
Kennesaw, GA 30152

Phone: 800-323-3329  
Fax: 330-544-8868

[www.nilesbldg.com](http://www.nilesbldg.com)