




“Specialists in Expanded Metal Building Products”

NILES NO. 66-N SHORT FLANGE ZINC CASING BEAD



Niles No. 66-N Short Flange Zinc Casing Bead	Length	Ctns/Pallet	Nominal Lbs/Ctn	Nominal Lbs/Plt
3/8"	10'	42	36	1512
1/2"	10'	42	38	1596
3/4"	10'	42	41	1722
7/8"	10'	42	44	1848
1"	10'	42	45	1890
1-1/4"	10'	42	49	2058
1-1/2"	10'	42	53	2226

30pcs/ctn – 300' per ctn

The Niles No. 66-N Short Flange Zinc Casing Bead has a short 90 degree turn at the plaster surface to neatly terminate plaster at the end of a wall or where it adjoins a dissimilar material.

ASTM B69-87 - Standard specification for flat rolled zinc. Approximately 99% pure zinc

ASTM C1063 - Standard specification for installation of lathing and furring for portland cement-based plaster

ASTM C841 - Standard specification for installation of interior lathing and furring

NILES BUILDING PRODUCTS CO.

Company Headquarters
1600 Hunter Street
Niles, Oh 44446

Dallas/Fort Worth Service Center
6400 Wuliger, Ste A
North Richland Hills, TX 76180

Southeast Distribution Center
1325 Cobb International Dr
Kennesaw, GA 30152

Phone: 800-323-3329

Fax: 330-544-8868

www.nilesbldg.com